

Name	NATURWAX
Description	Protective wax for floated and stucco finishes.
Main features	NATURWAX ; balanced blend of natural virgin waxes, emulsified with specific additives. NATURWAX is used for interiors to give shine and waterproof protection to the lime putty finishes or polished plasters type "stucco veneziano". It does not contain latex or organics resins, so it doesn't form a film and doesn't change the water vapour permeability of the product onto which it is applied.
Application cycle	NATURWAX is ready to use. During summer time the product may become too fluid. It is therefore advised to make it thicken in a refrigerator or in a cool place and mix it again. It can be applied using a rag, pad, or plastering trowel. Only a single very thin coat need to be applied. When it is properly dry buff up using a soft cloth, or orbital polisher operating at low rpm.
Practical advices	<ul style="list-style-type: none">▪ The product applied in excess can give white halos and anaesthetically effects. The product must be stored in the original tins at temperature included between +5°C and +30°C. Apply the product within 36 months from the production date.
Safety Precautions	<ul style="list-style-type: none">• Keep the tin tightly closed and protected from frost.• For safety precautions consult the relative safety data sheet.• User information is contained in the relevant safety sheet.• Empty containers and containers with traces of dried product film must be disposed of according to local regulations.
Tender item	Breathable and protective wax. Does not peel. NATURWAX Viero without latex and organic binders, with balanced blend of natural virgin waxes emulsified with specific additives, to apply in only one very thin coat with an average consumption of about 0.066 L/m ² . Suitable for the protection and polishing of lime putty finishes and polished plasters type "stucco veneziano" applied in interiors.



Specifications and other technical information	Method	Main Data at 20°C and 60% Relative Humidity
Coat finish and aspect		–
Density g/ml	MPL 007 (UNI 8910)	0,780 ÷ 0,820
Viscosity		Paste
Calculated spreading rate sq. m/l	MPL 059	15
Flash point °C	MPL 046 (UNI 8909)	Not flammable
Shelf life (in cool and dry place)	MPL 064 (UNI 10154)	At least 36 months
Exteriors/Interiors		No / Yes
Tool cleaner		White spirit odourless
Thinning % Volume		Ready-to-use
Application		Pad / trowel

All the technical data herein contained are fruit of our best experience and have indicative value and do not constitute guarantee of result. All the information and data reported herein are subject to variation at any time according to the latest development in the production technology. The application of the product is carried out beyond our control and it is therefore under the exclusive responsibility of the client. The correct use of the products implies the compliance of the GENERAL prescriptions of use and in particular those indicated on this data sheet, particularly concerning the suitability and preparation of the substrates. The technical service of MATERIS PAINTS Italia S.p.A. is at the user disposal for the supply of any integrative information required.
THIS DATA SHEET ANNULS AND SUBSTITUTES ANY PREVIOUS VERSION.



M.P.I. S.p.a.

Sede Legale: Via Nino Bixio, 47/49
 20026 Novate Milanese (MI) ITALY
 Tel. 199119955 Fax 199119977

Sede Commerciale:
 Via Provinciale, 309
 21030 Cassano Valcuvia (VA) - Italy
 Tel. (+39) 0332.999311 - Fax (+39) 0332.999399